

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number  
**WO 2005/078244 A3**

(51) International Patent Classification<sup>7</sup>: **F01L 13/00**

[JP/JP]; c/o Honda R & D Co., Ltd., 4-1, Chuo 1-chome, Wako-shi, Saitama 3510193 (JP).

(21) International Application Number:  
PCT/JP2005/002965

(74) Agents: **OGURI, Shohei** et al.; Eikoh Patent Office, 13th Floor, ARK Mori Building, 12-32, Akasaka 1-chome, Minato-ku, Tokyo 1076013 (JP).

(22) International Filing Date: 17 February 2005 (17.02.2005)

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:  
2004-040247 17 February 2004 (17.02.2004) JP  
2004-040246 17 February 2004 (17.02.2004) JP

(71) Applicant (for all designated States except US): **HONDA MOTOR CO., LTD.** [JP/JP]; 1-1, Minami-Aoyama 2-chome, Minato-ku, Tokyo 1078556 (JP).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **TASHIRO, Masahiko**

[Continued on next page]

(54) Title: VALVE TRAIN FOR INTERNAL COMBUSTION ENGINE



(57) Abstract: A valve train includes a primary rocker arm 50 oscillating about a primary oscillating center line L4 in response to the rotation of an inlet cam 21, a secondary rocker arm 60 oscillating about a secondary oscillating center line L5 so as to transmit a valve drive force via the primary rocker arm 50 to the inlet valve 14 and a holder 30 which supports the primary and secondary rocker arms 50, 60 in an oscillatory fashion in such a manner that the primary and secondary oscillating center lines L4, L5 oscillate together. A cam profile 55 has a lost motion profile 55a and a drive profile 55b formed on an abutment portion 54 of the primary rocker arm 50. A sectional shape of the lost motion profile 55a is an arc-like shape which is formed about the primary oscillating center line L4.

WO 2005/078244 A3



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,  
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

**(88) Date of publication of the international search report:**

13 October 2005